

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/096163 A1

(51) International Patent Classification⁷: **G06F 13/38**,
3/12, H04L 12/28

(21) International Application Number:
PCT/JP2005/006569

(22) International Filing Date: 29 March 2005 (29.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-099731 30 March 2004 (30.03.2004) JP

(71) Applicant (for all designated States except US): **CANON
KABUSHIKI KAISHA** [JP/JP]; 3-30-2, Shimomaruko,
Ohta-ku, Tokyo, 1468501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HASEGAWA, Reiji**

[JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2,
Shimomaruko, Ohta-ku, Tokyo, 1468501 (JP). **SUZUKI,
Takeshi** [JP/JP]; c/o CANON KABUSHIKI KAISHA,
3-30-2, Shimomaruko, Ohta-ku, Tokyo, 1468501 (JP).


(74) Agent: **OHTSUKA, Yasunori**; 7th FL., Shuwa Kioicho
Park Bldg., 3-6, Kioicho, Chiyoda-ku, Tokyo 1020094
(JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: IMAGE PROCESSING APPARATUS AND IMAGE PROCESSING SYSTEM AND ITS CONTROL METHOD



(57) Abstract: An image processing apparatus connected with a wireless LAN unit having a USB host controller via a USB interface, which performs data transmission/reception to/from a PC included in a network with which the communication terminal is connected. A data-receiving request is issued to the wireless LAN unit via the USB interface, then, in correspondence with a data-request command sent from the wireless LAN unit in response to the data-receiving request, information related to the network, arranged by input from an operation unit, is transmitted to the wireless LAN unit. Communication with the PC is performed via the wireless LAN unit by using the information related to the network.

WO 2005/096163 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IL, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.